

ATOMIZER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of the priority date of Provisional United States Patent Application Serial Number 60/271,947 filed February 28, 2001 for subject matter disclosed therein.

FIELD OF THE INVENTION

The present invention relates, in general, to a fluid delivery system. More particularly, this invention provides an integrated fluid delivery system (IFDS) for providing high purity fluid streams, such as for a wafer processing chamber.

BACKGROUND OF THE INVENTION

High purity fluid delivery systems are employed in demanding manufacturing environments such as the semiconductor manufacturing industry. The delivery systems are designed to precisely dispense fluids which may be hazardous in nature (i.e., corrosive, poisonous) and/or expensive. For example, in semiconductor processing/manufacturing, various stages such as low pressure chemical vapor deposition (LPCVD), oxidation, and plasma enhanced chemical vapor deposition (PECVD), require corrosive precursors such as boron, silicon and phosphorous to be delivered to a wafer processing chamber for the manufacture of semiconductor devices.

Typically, high purity fluid systems in the semiconductor manufacturing industry employ a complex network of tubing (plumbing) that require high integrity welds between tube sections and conduit assemblies for channeling the

fluids to a variety of fluid control, metering, and operational devices. As the layout of each system is dependent upon the number and location of the control, metering and operational devices, the "system schematic" is equal in complexity to the number of high integrity welds and corresponding conduit arrangement.

5 As can be appreciated, the number of high cost conduit assembly (i.e., valving) and high integrity welding connections, as well as the increased complexity of the corresponding system schematic leads to liquid delivery systems which are costly to both maintain and manufacture. Indeed, bulky conduit assemblies requiring even a mere additional square foot can be cost
10 prohibitive in the valuable real estate of clean room environments, where the cost to build per square foot is especially expensive.

Moreover, repairing a faulty weld or replacing a flow device component often necessitates disassembly of a substantial portion of the liquid delivery system. This also increases the down time of the process incorporating the
15 component. For example, there is shown in FIG. 1, a typical prior art liquid delivery system 5. Liquid delivery system 5 utilizes a conduit assembly 7 which employs a plurality of conduit sections 10, high integrity welds (not shown) and flow devices 12 for delivering high purity liquid streams from system 5. Flow devices 12 can be any device known in the art for processing a fluid, but
20 typically include flow controllers, valves, filters and pressure transducers. As shown in FIG. 1, conduit based system 7 requires a large degree of available area inside the cabinet of liquid delivery system 5. Thus, in the case where a particularly hard to reach component or weld requires maintenance and/or replacement, a significant portion of system 7 would need to be disassembled.
25 As can be appreciated, conduit system 7 is complex and costly to assemble and operate. For example, conduit system 7 has a higher overall resistance to fluid flow than lesser complex systems, thus an increased "down time" is required to purge the system of fluids where necessary.

To provide a precise volume of fluid to a processing application, fluid
30 delivery systems may comprise a flow controller. Typically, flow controllers couple a sensor for measuring flow volume with a valve for adjusting flow volume. Measuring the flow volume of an entire fluid stream, however, can lead to long response time. Some flow controllers employ a fluid bypass,

measuring the flow volume of a small portion of the flow and inferring the flow volume in the bypass. These flow controllers, however, employ methods for maintaining the necessary pressure differential that are expensive, have high part counts that add tolerances and cost, or are difficult to manufacture yielding
5 inadequate accuracy or repeatability. Examples of such bypass flow controllers include those using a bundle of tubes or a sintered metal slug.

Additionally, atomizing and/or vaporizing a liquid in a gas stream is often necessary in high purity fluid processing applications. For example, these processes may be employed to deposit high-purity, metal oxide films on a
10 substrate. Moreover, the liquid mixtures may also be utilized for spray coating, spin coating and sol-gel deposition of materials. In particular, chemical vapor deposition (CVD) is an increasingly utilized high purity fluid delivery process for forming solid materials, such as coatings or powders by way of reactants in a vapor phase. Typically, a reactant vapor is created by heating a liquid to an
15 appropriate temperature and bubbling a flow of carrier gas through the liquid (i.e. high purity fluid stream) to transport the vapor into a CVD chamber. Specifically, a gas stream and liquid stream are introduced into a single channel or conduit at a T-junction. The CVD system pumps a fluid stream at a steady, controlled rate into a hot region which may include ultrasonic energy for
20 effecting the mixture components. However, this technique creates a dead volume of material upon discontinuance of the process. Further, bubbling can often be an unpredictable method of vaporization, in which the precise quantity of the liquid reactant is difficult to control.

Accordingly, there is a need for an atomizer which predictably atomizes a
25 fluid while eliminating dead volume upon discontinuance of the atomization process. Also, there is a need for an accurate, reliable and inexpensive flow controller. Similarly, there is a need for an integrated liquid delivery system wherein the system schematic can be consolidated to a single modular manifold device.

SUMMARY OF THE INVENTION

The present invention provides an atomizer for precisely combining separate gas and liquid streams. A base member of the atomizer has a mixing

slot formed therein for producing a venturi effect at a mixing point. The mixing slot has a gas input side and a mixture side. A liquid inlet is in fluidic communication with the mixing slot. The mixing point is defined by the junction of the liquid inlet to the mixing slot. A gas stream inlet is in fluidic communication with the gas input side of the mixing slot. A mixture outlet is in fluidic communication with the mixture side of the mixing slot. The gas stream flowing into the mixing point is accelerated by the tapered mixing slot, drawing portions of the liquid into the gas stream by venturi effect to produce a mixture of atomized liquid and gas in a generally laminar flow. The atomized mixture of gas and liquid streams is presented at the mixture outlet.

It is to be understood that both the foregoing general description of the invention and the following detailed description are exemplary, but are not restrictive, of the invention.

BRIEF DESCRIPTION OF THE DRAWING

The invention is best understood from the following detailed description when read in conjunction with the accompanying drawing. Accordingly, the present invention will now be described by way of non-limiting examples with references to the attached drawing, in which:

FIG. 1 is a perspective view of a prior art Fluid Delivery System;

FIG. 2 is a perspective view of the manifolded fluid delivery system in accordance with one embodiment of the present invention;

FIG. 3 is an exploded view of the manifold assembly of the fluid delivery system in accordance with FIG. 2;

FIG. 4 is a perspective view of the manifold assembly of Fig. 3 showing seamless slots in phantom;

FIG. 5 is a sectional view of the manifolded fluid delivery system of FIGS. 1-4 taken along lines 3-3 of FIG. 3;

FIG. 6A is an enlarged view of the area designated by reference numeral 27 of FIG. 4.;

FIG. 6B is a sectional view taken along lines 6B of Fig. 6A;

5 FIG. 7 is a system schematic of the manifolded fluid delivery system of Fig. 2;

FIG. 8 is a bottom exploded view of the manifold assembly of a multilayered manifolded fluid delivery system in accordance with one embodiment of the present invention;

10 FIG. 9 is a longitudinal sectional view of a flow controller for use in an integrated fluid delivery system according to one embodiment of the present invention;

FIG. 10A is an exploded perspective view of a sub-assembly of the flow controller of Fig. 9;

15 FIG. 10B is an exploded perspective view of a sensor channel for the flow controller of Fig. 9;

FIG. 11 is a system schematic of the embodiment of the present invention shown in FIG. 9;

FIG. 12 is a top view of a mixing slot of an atomizer in accordance with an embodiment of the present invention;

20 FIG. 13 is an exploded view of an atomizer/vaporizer in accordance with an exemplary embodiment of the present invention; and

FIG. 14 is a heat exchanger for use in an integrated fluid delivery system in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Certain terminology used in the following description is for convenience only and is not limiting. The words “right,” “left,” “lower,” and “upper” designate directions in the drawings to which reference is made. The words “inwardly” and “outwardly” refer to directions toward and away from, respectively, the geometric center of the liquid delivery system and manifold in accordance with the present invention and designated parts thereof. The terminology includes the words noted above as well as derivatives thereof and words of similar import. The term “seamless” is generally defined as designating a continuous slot surface connecting corresponding manifold apertures.

I. Single Sided Manifold

In accordance with the present invention, an integrated fluid delivery system (IFDS) is provided to dispense fluid streams. In an exemplary embodiment, the fluid streams are of high purity. The high purity fluid streams are typically utilized to manufacture semiconductor devices and typically process such fluids as silicon, boron and phosphorous precursors for delivery to a processing destination, such as a wafer processing chamber. Those skilled in the art will recognize, however, that the present invention is applicable to any number of fluid stream chemistry and/or manufacturing environments.

Referring now to the figures in detail, wherein like numerals indicate like elements throughout, there is shown in FIGS. 2-6B, a manifolded fluid delivery system 15 in accordance with the present invention. Fluid delivery system 15 includes a first modular manifold or “base” 16 for internally channeling the high purity fluid streams along seamless integrated slots 18 (shown best in FIG. 3) formed therein.

As shown in the exemplary embodiment, base 16 is a substantially planar, rectangular substrate or plate having first and second surfaces 20 and 22, respectively. Other shapes of base 16 can be used depending on the application.

In an exemplary embodiment, base 16 is formed of stainless steel type 316L VAR (low carbon vacuum arc re-melt) selected for its high corrosion resistance. Other materials suitable for the fluids used in a particular application will be understood by those skilled in the art. The thickness of base 16 is suitable to the application and/or volume of chemicals to be processed therethrough.

One or more flow/processing devices 12 are mounted on respective interconnects 24. Interconnects 24 are mounted to base 16 via a mounting means, such as bolts (not shown), that are positioned through mounting holes 26. In an exemplary embodiment, mounting bolts are bolted to threaded interconnect apertures 28. In an exemplary embodiment, interconnects 24 are removable to allow for repair, maintenance, replacement or redesign of the IFDS and/or its component parts.

As shown in FIG. 3 and FIG. 4, base 16 includes at least one, and typically a plurality of seamless slots 18 (i.e., integrated seamless slots), interconnect apertures 28 (FIG. 4), and slot porting apertures 30 (FIG. 4) that are all formed on at least one of two major surfaces or faces thereof. In an exemplary embodiment, slot porting apertures 30 are metallic sealed. Other materials may be suitable for the seals, depending upon the application. Interconnect apertures 28 which may be threaded are arranged in a flow device footprint adapted for receiving an interconnect for mounting a corresponding flow device 12. One or both of first and second surfaces 20 and 22 can include seamless slots 18.

Seamless slots 18 are provided to consolidate a system schematic, such as shown in FIG. 7 onto surfaces 20 and/or 22 of base 16 for providing a modular manifold component. The depth of slots 18 is suitable to the application and/or volume of chemicals to be processed therethrough. In an exemplary embodiment, the system schematic is confined to a first surface 20 and seamless slots 18 are generally substantially elliptical in cross section. In another exemplary embodiment, seamless slots 18 are conical in cross section truncated with a tangential rounded radius as shown in FIG. 5.

Seamless slots 18 may be chemically etched and polished to avoid particulate entrapment. In an exemplary embodiment, seamless slots 18 are polished down to less than 16 rms for removing the grain structure of the metal surface of base 16. The metal surface of base 16 can be polished by extruding a polymer loaded with abrasives through base 16 at a high pressure through the use of polyurethane mill tooling. The unique shape of slots 18 is designed to complement the tooling for finishing purposes. Rectangular slots diminish the polishing ability of the mill tooling as rectangular slots have sharp corners that are difficult to access. Alternatively, seamless slots 18 may be formed by machining or other methods known in the art.

As shown in FIG. 4, seamless slots 18 include, along surfaces thereof, first slot porting apertures 30 extending from a surface of seamless slots 18 through to another base surface (22 in FIG. 4), for channeling high purity fluid streams therethrough.

As shown best in FIGS. 5, 6A, and 6B slot porting apertures 30 are finished with a detail 32 or "counterbore" to receive a corrosion-resistant seal. A corrosion-resistant seal such as a z-seal or c-seal, is used (in an exemplary embodiment, but not shown) upon connection of a corresponding flow device 12 or pneumatic control line. Corrosion-resistant seals, as used in an exemplary embodiment, require a higher tolerance finish (i.e., less than 16 rms) than that used for elastomeric fittings. The specifics of machining the appropriate finish for receiving the selected commercially available seal is understood by those skilled in the art. In some applications, it may be possible to use non-metallic, corrosion-resistant seals.

As shown in FIGS. 2 and 3, interconnects 24 are provided between both slot porting apertures 30 and a desired flow device 12. Interconnects 34 which may be attached to a low leakage fitting 36 (such as a VCR fitting manufactured by Swagelok Company of Solon, Ohio) as a single piece, are also provided between porting apertures 30 and desired flow device 12. Interconnect 34 is mounted to base 16 via mounting apertures 38 (bolts not shown). Interconnects 24 are typically commercially available fittings such as those

manufactured by Swagelok Company of Solon, Ohio having a detail corresponding to that of apertures 30 for seating the corrosion-resistant seal. Base 16 receives interconnects 24 by way of bolting through interconnect apertures 28. In an exemplary embodiment, a commercially available corrosion-resistant seal (not shown) is constructed of nickel and is interposed between apertures 30 and interconnect 24 for forming a compression fitting. The material of the seal should be a softer metal with respect to base 16 so that upon seating interconnect 24 on base 16 the seal is compressed and deforms to seal the connection upon bolting or other securing means.

A face plate 40 is shown in FIG 3, having a first and second surface. Face plate 40 is sealed or joined to first surface 20 of base 16 for enclosing seamless slots 18. Face plate 40 can be sealed to either first or second surface 20 or 22 of base 16 depending upon the application. A brazing medium 42 is disposed between base 16 and faceplate 40 and is utilized to seal face plate 40 to a desired surface of base 16 by brazing. In an exemplary embodiment, a nickel brazing medium 42 is used for the brazing process and base 16 is secured to face plate 40 by vacuum brazing. In this way, face plate 40 is joined with base 16, so that a first surface of face plate 40 abuts a surface (such as first surface 20) of base 16.

Face plate 40 may additionally include corrosion-resistant sealed plate porting apertures 44 positioned to overlay slots 18 of base 16. In such an embodiment seamless slots 18 can be accessed by a processing destination such as a wafer processing chamber through or from flow device 12. Plate porting apertures 44 are likewise finished with a detail 32 (as shown in slot porting apertures 30 in FIGS. 6A and 6B) or "counterbore" to receive a corrosion-resistant seal (such as a z-seal or c-seal, not shown) upon connection of a corresponding flow device or pneumatic control line to introduce the fluid streams to base 16. The present invention can be practiced without employing corrosion-resistant sealed plate porting apertures 44. Moreover, the thickness of face plate 40 is a matter of design choice for maintaining non-deformity when securing instrumentation to any resident plate porting apertures 44.

In an exemplary operation, base 16 receives each of the high purity fluid streams at a corresponding corrosion-resistant sealed slot porting aperture 30 for transporting a fluid along seamless slots 18. Corrosion-resistant sealed porting apertures 30 receive, upon connection of a corresponding flow device or pneumatic control line or the like, fluid streams for transport of one or more fluids through seamless slots 18 of base 16.

Slot porting apertures 30 are in fluidic communication with additional slot porting apertures located along seamless slots 18, as well as plate porting apertures 44 for channeling high purity fluid streams between slots in different bases. In embodiments where face plate 40 may not employ plate porting apertures 44, fluid would flow along seamless slots 18 between corresponding slot porting apertures 30. Once mated to an interconnect fitting 24, fluid device 12 is in fluidic communication with a corresponding one of the high purity liquid streams of base 16.

As shown in FIG. 7, an entire system schematic can be consolidated to base 16 with the corresponding valving and flow devices interconnected thereto for eliminating the need for the bulky conduit assemblies of the prior art. In this way, base 16 provides a modular system schematic for dispensing the fluid streams from integrated fluid delivery system 15 to processing destination such as a wafer processing chamber or other device requiring fluid streams.

II. Multisided Manifold

In a further embodiment, a second base 16B is provided as shown in FIG. 8 having similar details as base 16. The features of second base 16B are identified by a reference numeral followed by the letter "B". Second base 16B also has a first and second surface 20B and 22B respectively. Second base 16B also includes integrated seamless slots 18B formed thereon for channeling a fluid stream therethrough. Second seamless slots 18B include, along surfaces thereof, second slot porting apertures (not shown) which are corrosion-resistant sealed porting apertures extending from the surfaces of the second slots 18B through the second base 16B. Second base 16B is sealed to an available side of face

plate 40 in the same manner as that of the embodiment shown in FIG. 3. Plate porting apertures 44 overlay the slot porting apertures of the integrated slots 18B and the faceplate is interposed between first base 16 and second base 16B so that interconnect apertures 28 and 28B are in alignment.

5 In an exemplary embodiment, slot porting apertures in second base plate 16B are in fluidic communication with slot porting apertures 30 which are also through first slots 18 and second slots 18B for channeling fluid streams therebetween.

10 A second face plate (not shown) is connected to first surface 20B of base 16B for sealing slots 18B. It will be understood by those skilled in the art that any number of base sections 16 can be layered in this manner depending upon the particular application and that the invention described herein is not limited to the illustration but used above for explanatory purposes only.

III. Liquid Mass Flow Controller

15 Referring now to FIGS. 9-11, an exemplary embodiment of the present invention is shown in which base 16C is interconnected with a flow processing device to form a flow controller 46.

20 As shown in FIG. 9, a liquid flow controller assembly 46 employs a base 16C and an interconnect plate 48. In an exemplary embodiment, base 16C includes a seamless slot 18C (best shown in Fig. 9) between base 16C and interconnect plate 48. As above, with respect to base 16, base 16C and interconnect plate 48 are joined together by a brazing medium 42 using a vacuum brazing process. In an exemplary embodiment, base 16C can be vacuum brazed, at slot face 20C directly to second face 45 (shown in Fig. 25 10A) of interconnect plate 48 of liquid flow controller assembly 46. Seamless slots 18C may be formed by machining, etching, or other processes known in the art. Base may be a plate (or slot plate) having two opposing surfaces or faces, one of these faces being slot face 20C. In this way, slot face 20C and second face 45 abut so that seamless slot 18C is sealed by the abutment.

Porting apertures 50 are formed within interconnect plate 48 positioned to align with seamless slot 18C and extending to the first face 43 of interconnect plate 48 to allow the flow of liquid into and out of, a formed sensor channel 52 (discussed below). In an exemplary embodiment, porting apertures 50 are corrosion-resistant sealed similar to those corrosion-resistant sealed apertures previously discussed herein. Porting apertures 50 may provide for a portion of the liquid stream to flow into and through the sensor channel of the flow controller. As such, porting apertures 50 may be finished with a detail 32 or "counterbore." Detail 32 is provided for receiving a corrosion-resistant seal (such as a z-seal or c-seal not shown) upon connection of a corresponding flow device or pneumatic control line to introduce or outlet, fluid streams between base 16C.

Flow controller 46 includes a sensor channel 52 (best shown in FIG. 9) for providing a pathway for a fluid stream of base 16C. Sensor channel 52 in sensor area 56 carries a portion of the fluid stream transported into base 16C, with the remainder to be carried along seamless slot 18C. Sensor channel 52 is provided for measuring a change in temperature or temperature gradient (ΔT) of the portion of fluid flowing therein across points A and B in FIG. 11.

Sensor channel 52, as shown in Figs. 9 and 10B, comprises a tube section in fluid communication with seamless slot 18C through porting apertures 50 in interconnect plate 48. In a preferred embodiment of the present invention, sensor channel 52 extend downwardly from seamless slot 18C through a sensor plate 49 and into a sensor area 56 of a sensor housing 61, such that sensor channel 52 is at a lower elevation than seamless slot 18C. Two temperature sensors 57 are mounted on sensor channel 52 with a heater 59 is mounted on the sensor channel between the temperature sensors. In an exemplary embodiment, the sensors and heater comprise wire windings wrapped about the tubing. The heater transfers heat to the fluid to raise the fluid temperature up to 30 degrees Celsius. In an exemplary embodiment, however, the fluid temperature is raised about 5 degrees Celsius to avoid degradation of certain precursors that may be used with flow controller 46. In an exemplary embodiment, the sensor channel

52 extends downwardly to reduce blockage of the sensor channel by gas bubbles carried in the fluid stream.

In an exemplary embodiment of the invention, buttons 53 are welded to the ends of sensor channel 52. Buttons 53 are positioned in counterbores in sensor plate 49, and corrosion-resistant seals are compressed between buttons 53 and interconnect plate 48. Spacers 55 may be positioned inside the corrosion-resistant seals. Then sensor plate 49 is fastened to interconnect plate 48, such as with bolts, and sensor housing 61 is fastened to sensor plate 49.

Slot porting aperture 51 is formed in seamless slot 18C, extending through base 16C and providing fluid communication between seamless slot 18C and flow control valve 54. Flow control valve 54 is operably connected to temperature sensors 57. The temperature difference (ΔT) infers the flow through seamless slot 18C, and this temperature difference is used to generate an output signal voltage. The flow controller 46 can be used to adjust the mass flow through the flow controller 46 by adjusting the opening of flow control valve 54. Control electronics adjust the opening of flow control valve 54 until the output signal voltage is equal to a predetermined set-point in the control electronics corresponding to a desired mass flow rate. In an exemplary embodiment, the set-point is determined by a variable resistor, such as a potentiometer. Flow control valve 54 may be a suitable valve for the particular application that can be electronically adjusted to provide a variable flow rate. In an exemplary embodiment, flow control valve 54 is a piezotranslator, in which stacked ceramic disks press against a flexible metal diaphragm to open or close the diaphragm against apertures in a fluid pathway. The pressure applied by the ceramic disks is proportional to a voltage applied to them. The flow rate is determined by the gap between the diaphragm and the flat surface having the apertures in it (up to about .002 inches in an exemplary flow control valve).

Referring more particularly to FIG. 11, a system schematic of base 16C and flow controller 46 is shown. Inlet 58 into base 16C is a high pressure inlet which branches into two separate pathways. The first pathway is seamless slot 18C for providing a bypass pathway or channel. The second pathway is sensor

channel 52. Flow valve 54 is in fluidic communication with seamless slot 18C for receiving the portion of fluid flowing through sensor channel 52 (which is proportional to the flow through seamless slot 18C) and the portion of fluid flowing through seamless slot 18C. Seamless slot 18C provides a pressure drop from points 1 to 2 in FIG. 11. Sensor channel 52 and seamless slot 18C are in fluidic communication with a low pressure outlet 60, through control valve 54.

The change in temperature across points A and B of sensor channel 52 corresponds to an actual fluid flow through the flow controller 46 and has a very low response time on the order of 3 seconds or less. This is an improvement over the simple sampling of a single fluid stream as such an arrangement yields very slow response time (e.g., 20 seconds). This arrangement provides a fast and accurate reading of fluid flow. This mass flow controller can be a modular component for use in an IFDS.

IV. Atomizer

In accordance with another exemplary embodiment of the present invention, an atomizer for combining separate gas and liquid streams is provided. This atomizer can be a modular component for use in an IFDS. A mixing point is defined by the junction of a liquid inlet to a mixing slot. A gas stream inlet is in fluidic communication with a side of the mixing slot. A mixture outlet defines the remaining side of the mixing slot. A gas stream flowing into the mixing point is accelerated to a high velocity, reducing pressure for drawing the liquid into the gas stream by venturi effect.

There is shown in FIG. 12 a mixing slot 62 of an atomizer 64 for combining separate gas and liquid streams. Mixing slot 62 has a mixing point 66 for atomizing a liquid stream into a gas stream. A stream of the high purity mixture of fluid and gas are utilized, for example, to deposit high-purity, metal oxide films on a substrate in processes such as semiconductor manufacturing. Moreover, the liquid and gas mixtures may also be utilized for spray coating, spin coating and sol-gel deposition of materials. Those skilled in the art will

recognize, however, that the present invention is applicable to any number of fluid/gas stream chemistry and/or manufacturing environments.

Atomizer 64 includes a base member 16D having a mixing slot 62 formed in a face thereof for producing a venturi effect at a mixing point 66. In the exemplary embodiment shown, base 16D is a substantially planar, rectangular substrate formed of type 316 stainless steel (low carbon vacuum arc re-milled) LVAR selected for its high corrosion resistance. Other shapes of base 16D can be used depending on the application, and other materials suitable for the fluids/gases used in a particular application may be used as will be understood by those skilled in the art. The thickness of base 16D is suitable to the application and/or volume of chemicals to be processed therethrough. An exemplary base member structure is shown in Fig. 12 and described below. Mixing slot 62 may be formed by machining, etching, or other processes known in the art.

Mixing slot 62 of base member 16D has a gas input side 82 and a mixture side 88. In an exemplary embodiment, mixing slot 62 is generally hourglass shaped. Gas input side 82 and mixture side 88 are each substantially triangular in shape and are in fluid communication through a throat joining their respective apices. A mixing point 66 is located at the throat of the hourglass shape. The venturi effect is caused by the narrowing of the gas input side 82 and mixture side 88 of the hourglass shape, which increases the velocity of the gas lowering the pressure and drawing liquid into the gas stream. The particular fluid dynamics of the venturi effect will be understood by those skilled in the art.

A liquid inlet 80 is in fluidic communication with mixing point 66 of mixing slot 62. Mixing point 66 is defined by the junction of liquid inlet 80 and mixing slot 62. A gas stream inlet 84 is in fluidic communication with gas input side 82 of mixing slot 62. A valve (not shown) proximate to mixing point 66 may be provided for controlling the introduction of a liquid stream through liquid inlet 80 and eliminating dead volume upon discontinuance of the process as it controls the entry of the liquid stream at mixing point 66. A mixture outlet

90 is in fluidic communication with mixture output side 88 of mixing slot 62. A face plate 40D abuts base member 16D sealing mixing slot 62.

The atomizer described herein may be provided as a modular component for use in an IFDS.

V. Atomizer/Vaporizer

In one exemplary embodiment, as shown in Fig. 13, a mixing slot for atomizing a liquid into a gas stream, and a mixture heating slot for vaporizing the atomized liquid in the mixture are combined to form a vaporizer 64E. A base member 16E has a mixing slot 62, as described above, formed in one of its faces for producing a venturi effect at a mixing point 66. A gas slot 70 and a mixture heating slot 72 are formed in base member 16E in fluid communication with the gas input side 82 and mixture side 88, respectively, of mixing slot 62. Base member 16E internally channels gas and fluid streams along seamless slots 70 and 72. In the exemplary embodiment shown, base 16E is a substantially planar, rectangular substrate having first and second surfaces 74 and 78, respectively. Other shapes of base 16E can be used depending on the application. In this exemplary embodiment, base 16E is formed of stainless steel type 316 LVAR (low carbon vacuum arc re-milled) selected for its high corrosion resistance. Other materials suitable for the fluids/gases used in a particular application will be understood by those skilled in the art. The thickness of base 16E is suitable to the application and/or volume of chemicals to be processed therethrough.

In an exemplary embodiment, gas slot 70 is provided having a gas inlet side 84 and a gas outlet side 86. Gas outlet side 86 of gas slot 70 is connected to gas input side 82 of mixing slot 62. In an exemplary embodiment, as shown in FIG. 13, gas slot 70 is a serpentine pathway for heating the gas stream to either a predetermined or adjustable temperature. The degree of heating is dependent upon the length of the pathway and type of gas, as well as other factors (e.g., gas velocity and temperature difference between gas and base). The gas stream

flowing into a mixing slot may be heated to reduce the heat required to be added to the mixture stream for vaporization.

FIG. 13 shows mixture heating slot 72 in fluidic communication with mixture side 88 of mixing slot 62. Mixture heating slot 72 has a mixture inlet 90 and a mixture outlet 92. Mixture heating slot 72 is connected to mixture side 88 of mixing slot 62. In operation a gas stream flows through gas slot 70, into mixing slot 62, and then to mixing point 66. The velocity of the gas stream is increased in velocity by the narrowing of gas input side 82 lowering the pressure at mixing slot 62 and generating a venturi effect. In this way, portions of the liquid stream are drawn into the gas stream to provide an atomized mixture of gas and liquid streams to mixture heating slot 72. The mixture stream is heated in mixture heating slot 72, vaporizing the atomized liquid in the mixture to form a vapor mixture which exits base 16E via outlet 92.

As shown in FIG. 13, gas slot 70 and mixture heating slot 72 are sealed within base 16E by a pair of faceplates 40. A brazing medium (not shown) may be utilized to seal face plates 40 to surfaces 74 and 78 of base 16E by brazing. In an exemplary embodiment, the brazing process is similar to the brazing process described herein. In an exemplary embodiment, a nickel medium is used for the brazing process and base 16E is secured to face plates 40 by vacuum brazing. Alternatively, faceplates 40 may be sealed to the base 16E by way of interconnect apertures 98 provided to receive bolts (not shown). Additionally face plates 40 may include porting apertures 100 for importing and exporting fluid and/or gas streams directly to base 16E, such as from a flow control valve (not shown). Porting apertures 100 are sealed with a corrosion-resistant seal in an exemplary embodiment. While vaporizer 64E is shown having a serpentine layout, it is recognized by those skilled in the art that gas slot 70 and mixture heating slot 72 may be any number of layouts for heating the gas and mixture, or be essentially straight where necessary.

VI. Vaporizer

In an exemplary embodiment of a vaporizer, a heat exchanger is provided in fluidic communication with a mixture stream, such as at mixture side 88 of mixing slot 62 of an atomizer as described above. The heat exchanger can encompass a single continuous pathway, such as mixture heating slot 72, as shown in Fig. 13. The heat exchanger may be in fluid communication with the outlet of an atomizer as described herein. The heat exchanger provides heat to an atomized liquid stream vaporizing the atomized liquid. Atomizing the liquid in a mixed stream of gas and liquid prior to vaporization lowers the temperature of vaporization, which may reduce degradation of certain liquid precursors.

The heat exchanger may be a serpentine pathway, as shown in Fig. 13, for heating the atomized mixture to a predetermined temperature for vaporization. The degree of heating is dependent, in part, upon the length of the pathway and atomized chemistry. Other heat exchanger configuration, however, are possible and are within the scope of the invention.

In another exemplary embodiment of the present invention, an alternate heat exchanger 94F, is shown in Fig. 14. Heat exchanger 94F may be used to vaporize atomized liquid in a mixture stream produced by an atomizer 64 or for vaporizing a liquid supplied to the inlet of heat exchanger 94F which is neither atomized nor mixed with a gas stream. Heat exchanger 94F includes a base 16F with an inlet 102 in fluid communication with a mixture outlet of an atomizer or an unatomized and unmixed liquid stream. A distribution slot 104 formed in a slot face 106 of base 16F is in fluid communication with inlet 102 and a plurality of seamless slots 18F formed in slot face 106. A plurality of cross-slots 108 are formed in face 106 intersecting the plurality of seamless slots 18F. The cross-sectional area of the seamless slots is small enough to prevent surface tension from beading the liquid, which would reduce contact with the heated surface and reduce efficient heat transfer. Liquid is turned into vapor by the application of heat. If liquid is heated in a single slot or channel, bubbles of vapor can form that will expand rapidly and push slugs of liquid to the outlet, causing spitting. The cross-slots allow vapor bubbles to find a path to the outlet without pushing a slug of liquid to the outlet. The cross-sectional area of the cross-slots 108 may

be larger than the cross-sectional area of the seamless slots 18F to capture slugs of liquid and further reduce spitting.

Although illustrated and described above with reference to certain specific embodiments, the present invention is nevertheless not intended to be limited to the details shown. Rather, various modifications may be made in the details
5 within the scope and range of equivalents of the claims and without departing from the spirit of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208